



DOCSIS 3.1 Cable Modem Router

with Wi-Fi 6, Switchable Frequencies
and Extended Downstream 1218 MHz

CODA5810Q



The CODA5810Q gateway is more than ready for every demanding application. Online game, virtual reality, 4K and 8K streaming, video conferencing...the CODA5810Q provides a flawless, stutter-free experience for it all. It supports DOCSIS 3.1 - up to 6 Gbps* downstream. Inside-the-home networking is equally powerful, with next generation Wi-Fi 6, 2.5G ports and more. And software-switchable upstream frequency supports today and tomorrow's return path.

Upgrade to a High-Split Returns

A software switchable return path lets you easily support upstream bandwidth needs today and tomorrow. Upgrade to the high-split (5-204MHz) return path to meet the increased upstream bandwidth demands of video conferencing, IoT and interactive services. And since its software switchable, you can cost-effectively upgrade customers to higher-tier upstream speeds without swapping out hardware or sending out a technician.

Extended Downstream to 1218MHz

Future proof your network and offer even faster speeds by expanding the downstream frequency range up to 1218MHz.

Key Features

- DOCSIS 3.1 2x2 OFDM/OFDMA
- DOCSIS 3.0 32x8 Channel Bonding
- Switchable Upstream: 5-85/5-204MHz
- Extended Downstream 1218 MHz
- 4x4 2.4GHz 802.11ax and 4x4 5GHz 802.11ax Dual-band Concurrent MU-MIMO Internal Antennas
- 16 SSIDs (8 SSIDs per Radio)
- Individual Configuration for each SSID
- One 2.5 GigE and two 1 GigE Ports
- TR-069, TR-369 and Remote Management
- Supports IPv4 and IPv6
- Hitron Ecosystem Support (OptiMy, HitronCloud, MyHitron+)
- Low Latency DOCSIS
- Plume HomePass OpenSync certified



Interfaces

- 1x RF F-Type 75Ω Female Connector
- 2x RJ-45 10/100/1000BASE-T Ethernet Ports
- 1x RJ-45 1/2.5GBASE-T Ethernet Port

Reception-Demodulation

- DOCSIS 3.1/3.0/2.0
- DOCSIS 3.1 Demodulation: Multi-carrier OFDM 16 to 4096QAM
- DOCSIS 3.1 Data Rate: Up to 10Gbps with 2 OFDM 192MHz Downstream Channels + 32 SC-QAM
- DOCSIS 3.0 Demodulation: 64QAM, 256QAM
- DOCSIS 3.0 Data Rate: Up to 1.2Gbps with 32 Bonded Downstream Channels
- Frequency (edge-to-edge): Switchable 108-1002MHz/258-1218 MHz
- Channel Bandwidth: 6MHz
- Signal Level: 15dBmV

Transmitter-Modulation

- DOCSIS 3.1/3.0/2.0
- DOCSIS 3.1 Modulation: Multi-carrier OFDMA BPSK to 4096QAM
- DOCSIS 3.1 Data Rate: Up to 1Gbps with OFDMA 96MHz Upstream Channels
- DOCSIS 3.0 Modulation: QPSK, 8QAM, 16QAM, 32QAM, 64QAM, and 128QAM (SCDMA only)
- DOCSIS 3.0 Data Rate: Up to 320Mbps with 8 bonded Upstream Channels
- Frequency: Switchable 5-85MHz / 5-204MHz
- Extended Downstream 1218MHz
- Upstream Transmit Signal Level: +11 to 65dBmV

Wi-Fi

Wi-Fi Characteristics

- 802.11a/b/g/n/ac/ax
- 4T4R 2.4GHz 11ax and 4T4R 5GHz 11ax Dual Band Concurrent MU-MIMO with 1.2Gbps + 4.8Gbps PHY Rate
- 20/40/80/160MHz Channel Bandwidth
- High Power Design for Multi-radio Co-location
- Supports Standard 5GHz UNII Bands

Wi-Fi Features

- Up to 8 SSIDs per Radio
- Prioritized QoS: WMM/WMM-PS
- Transmit Power Control by Service Provider
- WPS (Wi-Fi Protected Setup) PBC, PIN
- Airtime Fairness (ATF)
- Band Steering (BS)
- Dynamic Frequency Selection (DFS)
- Wi-Fi Output Power Range: Max permitted by FCC/IC

Wi-Fi Security

- WPA-PSK
- WPA2-PSK (TKIP/AES)
- WPA3-SAE

Routing Support

- Protocol Support: IGMP v3 for IPTV service capability
- MAC Address Filtering (IPv4/IPv6)
- IP Source/Destination Address Filtering (IPv4/IPv6)
- DHCP, TFTP and ToD clients (IPv4/IPv6)
- DHCP Server supports RFC 1541 (IPv4)
- DHCPv6 obtains Prefix from DHCPv6 Server through Prefix Delegation
- Firewall with Stateful Inspection (IPv4/IPv6)
- Hacker Intrusion Prevention and Detection
- Application Content Filtering (IPv4/IPv6)
- Complete NAT Software Implemented as per RFC 1631 with Port and Address Mapping (IPv4)
- DSLite Support for IPv4 In-home Support with IPv6 MSO Backbone
- 6RD Support for Quick IPv6 Deployment over IPv4 Backbone
- RIPv2 for Static IP Support
- LAN-as-WAN function for the deployment of standalone Wi-Fi Router mode

Management

- Protocol Support: TR-069, TR-369, TFTP, SSHv2, SNMP v2, v3
- Web-based GUI Control, Configuration and Management
- Power-on Self-Diagnostic
- Hitron-proprietary MIBs for Extended Support on DOCSIS, Router Management, and Wi-Fi Management
- MyHitron+ App Support or Plume HomePass*
 - Plume Cognitive Certification (*Coming soon*)
 - Plume SamKnows (*Upon request*)
 - Plume WorkPass (*Upon request*)
- HitronCloud and OptiMy Backend Support
- Plume App Configuration, Control and Management Backend Support

Mechanical

- LEDs: One Multi-colored LED
- Factory Default Reset Button
- WPS Button
- Dimensions: 251.5mm (H) x 74.3mm (W) x 230.8mm (D)
- Net Weight: 1850 +/- 10g

Electrical

- Input Power: 12VDC, 4.5A
- Power Adaptor: 100-240VAC, 50/60Hz
- Power Consumption: 4.92W (power saving), 22W (typ.), 38W (Max)
- Surge Protection
 - RF Input sustains at least 4KV
 - Ethernet RJ-45 sustains at least 4KV

Environmental

- Operating Temperature: 0°C (32°F) ~ 40°C (104°F)
- Operating Humidity: 10% ~ 90% (Non-condensing)
- Storage Temperature: -40°C (-40°F) ~ 60°C (140°F)

Regulatory Compliance

- RoHS
- CableLabs
- FCC Part 15 Class B Subpart B, Part 15.247, Part 15.407, Part 2.1091
- ICES-003 Issue 6, Class B
- RSS-102 Issue 5
- IC RSS-247 Issue 2, 2017-02 and RSS-Gen Issue 5, 2018-4
- Canada RSS-Gen Issue 5, Amendment 1, Mar 2019
- UL 62368-1
- cUL 62368-1-14



LTV F219020

*Switching App Management Tools requires a firmware update

Specifications subject to change without further notice. Product photo may differ.

DOCSIS 3.1 is a CableLabs standard for high speed Internet access that defines support for up to 6 Gbps downstream and 1 Gbps upstream. Actual cable operator network speeds will vary and will be less than the calculated maximum possible speeds. Actual upload and download speeds are affected by several factors including, but not limited to: the capacity of your cable operator's network, the services offered by your cable operator, cable and Internet network traffic, your computer equipment etc. Final speeds will also be limited by each device and the quality of its connection to the modem or router.

Trademarks owned by Hitron Technologies Inc. © 2023 Hitron Technologies Americas Inc. All rights reserved

P/N: CODA5810Q-D-002